

MicroClean UC wiperes gamma

STERIL RENRUMSKLUD

Steril 100% Polyester Klud
ISO Klasse 4-5
Cleanroom Class 10-100

- 100% Polyester klud
- Ultra Sonic skåret
- Indeholder meget få partikler
- Fungerer godt med IPA-Ethanol samt andre opløsningsmidler
- Produceret og pakket i ISO 4 renrum
- Fremragende til farmaceut – Biotec og Medicinal Industrien
- Trippelpakket
- Anbefalet til brug i ISO klasse 4 Renrum



VARENUMMER	STØRRELSE	PAKNING
MC-GA2323	23 x 23 cm	10 stk./pose, 30 poser/karton
MC-GA3030	30 x 30 cm	10 stk./pose, 30 poser/karton



TECHNICAL SPECIFICATION

Micro Clean UC wipes gamma

STERIL RENRUMSKLUD

PERFORMANCE CHARACTERISTICS

Basis weight (IEST-RP-CC 004.3)	130 g/m ² 130±5gsm
Thickness	0.42 ~ 0.56 mm
Absorbency (IEST-RP-CC 004.3)	Sorptive capacity 300- 380 ml/m ² Rate 1.0 seconds

CONTAMINATION CHARACTERISTICS

Nonvolatile residue, NVR (IEST-RP-CC 004.3) <i>short term extraction</i>	<i>DIW Extractant</i> (100 ml DI water at ambient temp. for 24 hrs) 0.00085 g/m ² <i>IPA Extractant</i> (100 ml IPA at ambient temp. for 24 hrs) 0.0095 g/m ²
Ion content (IEST-RP-CC 004.3) <i>short term extraction</i>	Sodium (Na) <0.032 ppm Calcium (Ca) <0.0821 ppm Chloride (Cl) <0.088 ppm

RELEASABLE PARTICLES

LPC (> 0.5 um) (IEST-RP-CC 004.3-orbital shake mtd)	<3,0 x 10 ² particles/cm ²
APC (Helmke Drum Test_10rpm);>0.5 um (IES-RP-CC003.2)	<50 counts/pc./cfm

- MicroClean Gamma**

Each package is gamma irradiated to a Sterility Assurance Level (SAL) of 10⁻⁶.
A circular Red Sticker found on the packaging ensures sterilization of the wiper.

Opdateret: 22.11.2022